


MADHUS ER65 WHEEL BALANCER



EUROPEAN WHEEL BALANCER
WITH MADHUS SERVICE SUPPORT

MADHUS ER65

Premium Wheel Balancer at an Affordable price

- VDD Virtual Direct Drive very quick and maintenance free measurement system Patented
- Lock of wheel in the correction position by means of an electromagnetic brake
- Software programs for the professionals: SPLIT, OPT, ALU
- Extended gauge for diameter and distance measurement of rims up to 28" with new pincer to hold the adhesive weight
- ALU-S balancing mode (adhesive weights on the internal rim planes) with specific counterweight position indicator (position repeater)
- LASER for weight positioning inside the rim
- Automatic approach of the wheel within 15° from the point of application of the balancing weight, to allow the operator to position it correctly
- **ER65SE Pneumatic wheel locking** Floor to floor time reduction / Extremely easy and quick to use / Very accurate wheel centering Patented



Virtual Sonar

Innovative 3d software that calculates rim width



AutoAdaptive Mode

Innovative tolerance calculation system

TECHNICAL SPECIFICATION

| Single phase power supply | 115 / 230 V 50/60 Hz |
|------------------------------------|--------------------------|
| Max. absorbed power | 0,15 kW |
| Balancing speed | 100 rpm |
| Measuring cycle for 15 kg wheel | 4.7 s |
| Measurement uncertainty | 0,5 g |
| Avarage noise | < 70 dB (A) |
| Rim width setting range | 1.5" ÷ 20" / 40 ÷ 510 mm |
| Rim diameter setting range | 10" ÷ 30" / 265 ÷ 765 mm |
| Max. wheel weight | < 75 kg |
| Machine weight | 120 kg |

